

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/06/2015

Revision date: 04/06/2015

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Name : Kerosene Thermometer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Thermometer

1.3. Details of the supplier of the safety data sheet

GSC International, Inc.
1747 N. Deffer Drive
Nixa,
MO 65714
United States of America

Tel: 417-374-7431
Fax: 417-374-7442
Email: info@gscinternationalinc.com

1.4. Emergency telephone number

| Country | Organization/Company | Address | Emergency number |
|--------------------------|--|--|---|
| MEXICO | Servicio de Informacion Toxicologica Sintox | Tintoreto #32 Edif. a Desp. Col. Nochebuena Mixcoac México, D.F. | 1 800 009 2800 +52 55 5611 2634 /+52 55 5598 9095 |
| UNITED STATES OF AMERICA | American Association of Poison Control Centers | | 1-800-222-1222 |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226
Skin Irrit. 2 H315
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H226 - Flammable liquid and vapor
H315 - Causes skin irritation
Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/... equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|----------|--------------------|---------|---|
| kerosene | (CAS No) 8008-20-6 | 0 - 100 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Get medical advice/attention. If skin irritation occurs: Gently wash with plenty of soap and water.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : The product is stable at normal handling and storage conditions.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.
- Hygiene measures : Wash Skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Flame proof, lighting, electrical equipment and ventilation equipment.
- Storage conditions : Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat-ignition.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Kerosene Thermometer | | |
|----------------------|----------------|--|
| ACGIH | Not applicable | |
| OSHA | Not applicable | |

| kerosene (8008-20-6) | | |
|----------------------|--------------------------------|-----------------------|
| ACGIH | ACGIH TWA (mg/m ³) | 200 mg/m ³ |
| OSHA | Not applicable | |

8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation.
- Personal protective equipment : Protective clothing. Protective goggles.



- Hand protection : Not required for normal conditions of use.
- Eye protection : Where eye contact may occur from use, Wear eye protection.
- Skin and body protection : Not required for normal conditions of use.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Other information : Do not eat, drink or smoke during use.

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Color | : red |
| Odor | : No data available |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 175 - 325 °C |
| Flash point | : 38 °C |
| Auto-ignition temperature | : 210 °C |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : 1 mm Hg 20°C |
| Relative vapor density at 20 °C | : 4,5 |
| Relative density | : No data available |
| Specific gravity / density | : ≈ 0,84 g/cm ³ |
| Solubility | : insoluble in water. Water: Solubility in water of component(s) of the mixture : • : 0,0007 g/100ml |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosive limits | : 0,7 - 5 vol % |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable at normal handling and storage conditions.

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| kerosene (8008-20-6) | |
|-----------------------------|-----------------------|
| LD50 oral rat | > 5000 mg/kg (Rat) |
| LD50 dermal rat | > 2000 mg/kg (Rat) |
| LD50 dermal rabbit | > 2000 mg/kg (Rabbit) |
| LC50 inhalation rat (mg/l) | > 5,28 mg/l/4h (Rat) |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified (Based on available data, the classification criteria are not met) |
| Respiratory or skin sensitization | : Not classified (Based on available data, the classification criteria are not met) |
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met)Based on available data, the classification criteria are not met |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met) |

| kerosene (8008-20-6) | |
|-----------------------------|----------------------|
| IARC group | 3 - Not classifiable |

| | |
|---|--|
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met)Based on available data, the classification criteria are not met |
| Specific target organ toxicity (single exposure) | : Not classified (Based on available data, the classification criteria are not met) |
| Specific target organ toxicity (repeated exposure) | : Not classified (Based on available data, the classification criteria are not met) |
| Aspiration hazard | : Not classified (Based on available data, the classification criteria are not met) |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

| kerosene (8008-20-6) | |
|---|--------------------------------------|
| LC50 fish 1 | 18 - 25 mg/l (96 h; Pisces) |
| LC50 other aquatic organisms 1 | 1 - 100 mg/l |
| EC50 Daphnia 1 | 1,4 - 21 mg/l (Daphnia magna) |
| LC50 fish 2 | 45 mg/l (Pimephales promelas) |
| TLM fish 1 | 2990 ppm (24 h; Lepomis macrochirus) |
| Threshold limit other aquatic organisms 1 | 1 - 100 |
| Threshold limit algae 1 | 4 - 8,Algae |

12.2. Persistence and degradability

| Kerosene Thermometer | |
|-------------------------------|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |

| kerosene (8008-20-6) | |
|-------------------------------|--|
| Persistence and degradability | Biodegradable in water. Readily biodegradable in water in anaerobic conditions. Forming sediment in water. Biodegradable in soil. Biodegradable in soil in anaerobic condition. Adsorbs into the soil. |

12.3. Bioaccumulative potential

| Kerosene Thermometer | |
|-----------------------------|------------------|
| Bioaccumulative potential | Not established. |

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| kerosene (8008-20-6) | |
|---------------------------|----------------------|
| Log Pow | 3,3 - 6 (Calculated) |
| Bioaccumulative potential | bioaccumulative. |

12.4. Mobility in soil

| kerosene (8008-20-6) | |
|----------------------|-----------------|
| Surface tension | 0,02 - 0,03 N/m |

12.5. Other adverse effects

- Effect on ozone layer :
Effect on the global warming : No known ecological damage caused by this product.
Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

- In accordance with DOT
Transport document description : UN1223 Kerosene, 3, III
UN-No.(DOT) : UN1223
Proper Shipping Name (DOT) : Kerosene
Hazard Classes (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1223 KEROSENE, 3, III, (D/E)

Packing group (ADR) : III

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 30

Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code (ADR) : D/E

LQ : 5I

Excepted quantities (ADR) : E1

Transport by sea

UN-No. (IMDG) : 1223

Proper Shipping Name (IMDG) : KEROSENE

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No.(IATA) : 1223

Proper Shipping Name (IATA) : Kerosene

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

kerosene (8008-20-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226

Skin Irrit. 2 H315

Aquatic Chronic 2 H411

Kerosene Thermometer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R38

N; R51/53

R10

Full text of R-phrases: see section 16

15.2.2. National regulations

15.3. US State regulations


SECTION 16: Other information

| | |
|-------------------|--|
| Revision date | : 04/06/2015 |
| Data sources | : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. |
| Other information | : None. |

Full text of H-phrases:

| | |
|-------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| H226 | Flammable liquid and vapor |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H411 | Toxic to aquatic life with long lasting effects |

| | |
|--------------------|---|
| NFPA health hazard | : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given. |
| NFPA fire hazard | : 3 - Liquids and solids that can be ignited under almost all ambient conditions. |
| NFPA reactivity | : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water. |



HMIS III Rating

| | |
|---------------------|--|
| Health | : 1 Slight Hazard - Irritation or minor reversible injury possible |
| Flammability | : 3 Serious Hazard |
| Physical | : 0 Minimal Hazard |
| Personal Protection | : B |

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.